

Technische Daten Elektrokettenzug LIFTKET STAR

Tragfähigkeit (kg)	ISO	Type	Kettendicke (mm)	Hubgeschwindigkeit (m/min)	Aufhängung			Geschwindigkeiten (Elektrofahwerk)	Flanschbreite (mm)		
					Rollfahwerk	Hakenaufhängung	Elektrofahwerk		N (normal)	S1 (breit)	S2 (extra breit)
125	M7	125/1-8	5,2x15	8	✓	✓	✓	20/5	50-106	110-200	210-300
	M7	125/1-8/2	5,2x15	8/2	✓	✓	✓	20/5	50-106	110-200	210-300
250	M6	250/1-4	5,2x15	4	✓	✓	✓	20/5	50-106	110-200	210-300
	M6	250/1-8	5,2x15	8	✓	✓	✓	20/5	50-106	110-200	210-300
	M6	250/1-8/2	5,2x15	8/2	✓	✓	✓	20/5	50-106	110-200	210-300
	M6	250/1-18/4,5	5,2x15	18/4,5	✓	✓	✓	20/5	50-106	110-200	210-300
500	M4	500/1-4	5,2x15	4	✓	✓	✓	20/5	50-106	110-200	210-300
	M6	500/2-4/1	5,2x15	4/1	✓	✓	✓	20/5	50-106	110-200	210-300
	M5	500/1-8/2	7,2x21	8/2	✓	✓	✓	20/5	66-135	137-215	220-300
	M5	500/1-8	7,2x21	8	✓	✓	✓	20/5	66-135	137-215	220-300
1000	M5	1000/1-4	7,2x21	4	✓	✓	✓	20/5	66-135	137-215	220-300
	M5	1000/2-4/1	7,2x21	4/1	✓	✓	✓	20/5	66-135	137-215	220-300
	M5	1000/2-5/1,25	7,2x21	5/1,25	✓	✓	✓	20/5	66-135	137-215	220-300
	M5	1000/1-6	7,2x21	6	✓	✓	✓	20/5	66-135	137-215	220-300
	M5	1000/1-6/1,5	7,2x21	6/1,5	✓	✓	✓	20/5	66-135	137-215	220-300
	M6	1000/1-8/2	9x27	8/2	✓	✓	✓	20/5	82-155	137-215	220-300
1600	M5	1600/2-4	7,2x21	4	✓	✓	✓	20/5	66-135	137-215	220-300
	M5	1600/1-8	9x27	8	✓	✓	✓	20/5	82-155	137-215	220-300
	M5	1600/1-8/2	9x27	8/2	✓	✓	✓	20/5	82-155	137-215	220-300
	M5	1600/1-10/2,5	9x27	10/2,5	✓	✓	✓	20/5	82-155	137-215	220-300
2000	M5	2000/2-3	7,2x21	3	✓	✓	✓	20/5	66-135	137-215	220-300
	M5	2000/2-3/0,75	7,2x21	3/0,75	✓	✓	✓	20/5	66-135	137-215	220-300
	M6	2000/2-4/1	9x27	4/1	✓	✓	✓	20/5	82-155	137-215	220-300
	M5	2000/1-8/2	9x27	8/2	✓	✓	✓	16/4	82-155	160-236	230-310
2500	M5	2500/1-10	9x27	10	✓	✓	✓	16/4	82-155	160-236	230-310
	M5	2500/1-10/2,5	9x27	10/2,5	✓	✓	✓	16/4	82-155	160-236	230-310
3200	M5	3200/2-4	9x27	4	✓	✓	✓	20/5	82-155	137-215	220-300
	M5	3200/2-4/1	11,3x31	4/1	✓	✓	✓	20/5	82-155	137-215	220-300
	M3	3200/1-8	11,3x31	8	✓	✓	✓	16/4	82-155	160-236	230-310
	M3	3200/1-8/2	11,3x31	8/2	✓	✓	✓	16/4	82-155	160-236	230-310
4000	M5	4000/2-4/1	11,3x31	4/1	✓	✓	✓	16/4	82-155	160-236	230-310
	M5	4000/1-5,6/1,4	16x45	5,6/14	X	✓	✓	16/4	140-230	220-310	X
5000	M5	5000/2-5	11,3x31	5	✓	✓	✓	16/4	82-155	160-236	230-310
	M5	5000/2-5/1,25	11,3x31	5/1,25	✓	✓	✓	16/4	82-155	160-236	230-310
	M4	5000/1-5,6/1,4	16x45	5,6/1,4	X	✓	✓	16/4	140-230	220-310	X

Technische Daten Elektrokettenzug LIFTKET STAR

Tragfähigkeit (kg)	ISO	Type	Kettendicke (mm)	Hubgeschwindigkeit (m/min)	Aufhängung			Geschwindigkeiten (Elektrofahwerk)	Flanschbreite (mm)		
					Rollfahwerk	Hakenaufhängung	Elektrofahwerk		N (normal)	S1 (breit)	S2 (extra breit)
6300	M3	6300/2-4	11,3x31	4	✓	✓	✓	16/4	82-155	160-236	230-310
	M3	6300/2-4/1	11,3x31	4/1	✓	✓	✓	16/4	82-155	160-236	230-310
	M3	6300/1-5,6/1,4	16x45	5,6/1,4	X	✓	✓	16/4	140-230	220-310	X
7500	M3	7500/1-4,4/1,1	17,3x48	4,4/1,1	X	✓	✓	16/4	140-230	220-310	X
8000	M5	8000/2-2,8/0,7	16x45	2,8/0,7	X	✓	✓	16/4	140-230	220-310	X
	M5	8000/1-6,4/1,6	23,5x66	6,4/1,6	X	✓	✓	16/4	140-230	220-310	X
10000	M4	10000/2-2,8/0,7	16x45	2,8/0,7	X	✓	✓	16/4	140-230	220-310	X
	M4	10000/1-6,4/1,6	23,5x66	6,4/1,6	X	✓	✓	16/4	140-230	220-310	X
12500	M3	12500/2-2,8/0,7	16x45	2,8/0,7	X	✓	✓	16/4	140-230	220-310	X
	M3	12500/1-6,4/1,6	23,5x66	6,4/1,6	X	✓	✓	16/4	140-230	220-310	X
15000	M3	15000/2-2,2/0,6	17,3x48	2,2/0,6	X	✓	✓	16/4	140-230	220-310	X
16000	M5	16000/2-3,2/0,8	23,5x66	3,2/0,8	X	✓	✓	16/4	140-230	220-310	X
20000	M4	20000/2-3,2/0,8	23,5x66	3,2/0,8	X	✓	✓	16/4	140-230	220-310	X
25000	M3	25000/2-3,2/0,8	23,5x66	3,2/0,8	X	✓	✓	16/4	140-230	220-310	X