



## Hebeschlingen endlos nach CEN 1492-1, farbcodiert, SF 1 : 7

Nenntragfähigkeit kg			1000	2000	3000	4000	5000	6000	8000	10000
Farbe			violett	grün	gelb	grau	rot	braun	blau	orange
Breite mm			50	60	90	120	150	180	240	300
Nutzlänge (L1) m	Umf.-länge (L2) m	Best.-Nr. + Best.-End-Nr.	704001...	704003...	704004...	704005...	704006...	704007...	704008...	704009...
1,0	2,0	01								
2,0	4,0	02								
3,0	6,0	03								
4,0	8,0	04								
5,0	10,0	05								
6,0	12,0	06								
7,0	14,0	07								
8,0	16,0	08								

Andere Ausführungen auf Anfrage



61

## Rundschnngen doppelt ummantelt nach CEN 1492-2, farbcodiert, SF 1 : 7

Nenntragfähigkeit kg			1000	2000	3000	4000	5000	6000	8000	10000
Farbe			violett	grün	gelb	grau	rot	braun	blau	orange
Nutzlänge (L1) m	Umf.-länge (L2) m	Best.-Nr. + Best.-End-Nr.	70410001...	70410002...	70410003...	70410004...	70410005...	70410006...	70410008...	70410010...
0,5	1,0	01								
1,0	2,0	02								
1,5	3,0	03								
2,0	4,0	04								
2,5	5,0	05								
3,0	6,0	06								
4,0	8,0	08								
5,0	10,0	10								

Andere Ausführungen auf Anfrage



### Schnittbild

Schnittbild eines zweilagigen Schlauches mit PES-Fäden

